# **HOSE, CORD & CABLE REELS**





**MULTI-POSITION LOCK RATCHET** secures hose at desired length - Visible on other side

VERSATILE GUIDE ARM adjusts to wall, floor & ceiling mounting •

HIGH QUALITY ELECTRO-POLISHED NON-CORROSIVE STAINLESS STEEL CONSTRUCTION

*NON-CORROSIVE STAINLESS STEEL FLUID PATH featuring stainless steel swivel with non-toxic food grade grease* 

HEAVY DUTY STAINLESS STEEL SOLID SPUN DISCS WITH ROLLED EDGES - not stamped, made with first of its kind CNC robotic spinning cell -----

ENCLOSED FACTORY TUNED AND MATCHED CARTRIDGE-STYLE SPRING MOTOR for safe and easy maintenance

HEAVY GAUGE 1/4" STAINLESS STEEL BASE & SUPPORT POST for maximum stability

# POSSIBLE FIELDS OF APPLICATION

- Hygenic Environments
- Food & Chemical Processing Plants
- Corrosive Environments Processing Plants
   Food Grade Washdown Pulp & Paper Plants
- Bottling Plants
- Meat Packing



F: 480.820.5132 E:



COXREELS

# Food & Chemicals



63/4 x 185/8 x 171/8

63/4 x 185/8 x 171/8

PS

300

300

PSI

3,000

3,000

PSI

300

6,000

FT

100

200

FT

50

50

3⁄8'

3/8'

I.D.

APRX. LBS.

70

83

APRX. LBS

43

43

WxHxL

281/8 x 261/8 x 24

365/8 x 261/8 x 24"

WXHXL

71/8 x 185/8 x 175/8'

71/8 x 185/8 x 175/8"

50

APRX. LBS

34

39



### SS-P, SS-SH & SS-MP SERIES

<ul> <li>Non-corrosive external fluid path with machined from high</li> </ul>	
quality stainles steel 90° full-flow NPT swivel inlet	
<ul> <li>Swivel Seals: NITRILE with Non-Toxic Food Grade Grease</li> </ul>	

- Sturdy single
- design facilita • SH/MP Series axle support

- OWIVELOGAIS, NITHIEL WITH NUTHING FUUL GLAUG GLEASE						
	P-LPL-425-SS	1/2"	25	300	39	7 x 185⁄8 x 171⁄8"
Sturdy single pedestal spring driven reel with space saving	SHL-N-350-SS	3⁄8"	50	300	44	81/4 x 211/4 x 191/2"
design facilitates workplace organization	SHL-N-450-SS	1/2"	50	300	46	81⁄4 x 211⁄4 x 191⁄2"
<ul> <li>SH/MP Series features Coxreels' exclusive Super Hub<sup>™</sup> dual</li> </ul>	SHL-N-525-SS	3⁄4"	25	300	45	93/8 x 211/4 x 191/2"
axle support system	MPL-N-350-SS	3⁄8"	50	3,000	53	81⁄4 x 211⁄4 x 191⁄2"
	MPL-N-450-SS	1/2"	50	3,000	53	81/4 x 211/4 x 191/2"
SS-T SERIES						
Non-corrosive external fluid path with machined from high	MODEL	I.D.	FT.	PSI	APRX. LBS.	WxHxL
quality stainles steel 90° full-flow NPT swivel inlet	TSHL-N-4100-SS	1/2"	100	300	80	93/8 x 251/2 x 24"
Swivel Seals: NITRILE with Non-Toxic Food Grade Grease	TSHL-N-550-SS	3⁄4"	50	300	70	91/8 x 251/2 x 24"
<ul> <li>Sturdy dual pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system</li> </ul>						
SS-EN SERIES						
			r	·		r
<ul> <li>Non-corrosive external fluid path with machined from high</li> </ul>	MODEL	I.D.	FT.	PSI	APRX. LBS.	WxHxL

3⁄8'

3/8

MODEL

P-LPL-335-SS

P-LPL-350-SS



#### **SS-EN SE**

Non-corrosive external fluid path with machined from high	MODEL	I.D.	FT.	PSI	APRX. LBS.	WxHxL
quality stainles steel 90° full-flow NPT swivel inlet	ENL-N-335-SS	3⁄8"	35	300	46	61 x 181 x 19"
Swivel Seals: NITRILE with Non-Toxic Food Grade Grease	ENL-N-350-SS	3⁄8"	50	300	58	81/2 x 213/4 x 217/8"
Sturdy enclosed reel for aesthetic purposes & greater hose	ENL-N-450-SS	1/2"	50	300	61	8½ x 21¾ x 21%"
protection						



#### SS-100 SERIES

	Non-corrosive external fluid path with machined from high	MODEL	I.D.	FT.	PSI	APRX. LBS.	WxHxL
	quality stainles steel 90° full-flow NPT swivel inlet	112-4-75-SS	1/2"	75	4,000	21	22¾ x 13 x 12"
	Swivel Seals: NITRILE with Non-Toxic Food Grade Grease     Salid and piece heavy gauge steel "III" shared from:	117-4-225-SS	1/2"	225	4,000	31	223⁄4 x 18 x 17"
		117-5-100-SS	3⁄4"	100	4,000	36	231⁄4 x 18 x 17"

Solid one piece, heavy gauge steel "U" shaped frame



#### SS-1125 SERIES

Non-corrosive external fluid path with machined from high	MODEL	MOTOR OPTION	I.D.	FT.	PSI	APRX. LBS.	WxHxL
quality stainles steel 90° full-flow NPT swivel inlet	1125-4-100-SS	Electric Motor	1⁄2"	100	3,000	36	19½ x 18¾ x 175⁄8"
<ul> <li>Swivel Seals: NITRILE with Non-Toxic Food Grade Grease</li> </ul>	1125-4-200-SS	Options	1/2"	200	3,000	39	25½ x 18¾ x 175/8"
• Exclusive low profile outlet riser & open drum slot design for flat	1125-5-100-SS	•	3⁄4"	100	3,000	42	26¾ x 18¾ x 175⁄8"
smooth hose wrap	1125-5-200-SS	Available	3⁄4"	200	3,000	55	38¾ x 18¾ x 175⁄8"
Should hose wap							

MODE

1175-6-100-SS 1175-6-200-SS

MODEL

EZ-P-BLL-350

EZ-P-BHL-350

MOTOR OPTION

Electric Motor

options available

#### SS-1175 SERIES

- Non-corrosive external fluid path with machined from high quality stainles steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE with Non-Toxic Food Grade Grease
- · Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap

CHOICE OF MOTORS	Option - A	Option - AB Air Motor	Option - E & EF	Option - EA, EB & ED	Option - H
1125 & 1175	4 Gast	6 Gast	12V & 24V Motor	Explosion Proof 12V, 24V & 115V	Motor Motor



#### PURE FLOW EZ-P SERIES

- · Non-corrosive stainless steel air/fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE with Non-Toxic Food Grade Grease
- · Sturdy single pedestal reel with space saving design facilitates workplace organization



# PURE FLOW EZ-T SERIES

- · Non-corrosive stainless steel air/fluid path with machined from MODEL I.D. FT PSI APRX, LBS WXHXL high quality stainless steel 90° full-flow NPT swivel inlet EZ-T-BLL-3100 3/8' 50 300 85 93/8 x 251/2 x 24 • Swivel Seals: NITRILE with Non-Toxic Food Grade Grease EZ-T-BHL-3100 3/8' 50 6,000 85 93/8 x 251/2 x 24
- · Sturdy dual pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system



#### PURE FLOW 1125 SERIES

Non-corrosive stainless steel air/fluid path with machined from	MODEL	I.D.	FT.	PSI	APRX. LBS.	WxHxL	
high quality stainless steel 90° full-flow NPT swivel inlet	1125P-4-6	1/2"	100	6,000	36	19¾ x 185% x 175%"	
Swivel Seals: NITRILE with Non-Toxic Food Grade Grease	1125P-4-8	1/2"	150	6,000	37	21¾ x 185⁄8 x 175⁄8"	
Exclusive low profile outlet riser & open drum slot design for fl	at 1125P-4-12	1/2"	200	6,000	39	25¾ x 18% x 17%"	
smooth hose wrap This calentian only represente a sample of products applicable in this inductor. Please visit us policy or eacy of the factory for more product option							

This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.

#### www.coxreels.com 800.COX.REEL P: 480.820.6396 F: 480.820.5132

E: info@coxreels.com