

# Pest Control

## PROFESSIONAL GRADE FEATURES



**HEAVY DUTY SOLID SPUN DISCS WITH ROLLED EDGES** - not stamped, made with first of its kind CNC robotic spinning cell

**LOW PROFILE RISER & OPEN DRUM SLOT** for smooth, even hose wraps

**ZINC PLATED PLUMBING** for applications requiring superior oxidation prevention  
Only on 1/2" 1125 Series

**INDUSTRIAL GRADE BRASS**, machined from solid, full flow swivel with external fluid path for ease of seal maintenance

**PERMANENTLY SEALED PILLOW BLOCK BEARINGS** for smooth rotation

**ONE PIECE ALL CNC ROBOTICALLY WELDED** steel "A" frame construction

### MOTORIZED VERSIONS:

The electric version features all of the same features found on the hand crank model plus **SOLID STEEL HALO** is welded to the disc for a direct gear driven motor



### POSSIBLE FIELDS OF APPLICATION

- Pest Control
- Chemical Spraying
- Lawn Spraying
- Ground Maintenance
- Agricultural Spraying
- Skid Sprayer Units



[www.coxreels.com](http://www.coxreels.com)

800.COX.REEL

P: 480.820.6396

F: 480.820.5132

E: [info@coxreels.com](mailto:info@coxreels.com)



## 1125 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 1" models)
- Swivel Seals: NITRILE (AFLAS on 1" models)
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap
- All welded steel "A" frame construction for superior reel structure
- For Stainless Steel swivel with Viton® seals & fluid path add suffix "-BBXX"



MODEL	MOTOR OPTION	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125-4-100	Electric Motor Options Available	1/2"	100	3,000	36	19 1/2 x 18 3/4 x 17 5/8"
1125-4-200		1/2"	200	3,000	39	25 1/2 x 18 3/4 x 17 5/8"
1125-4-325		1/2"	325	3,000	48	31 1/2 x 18 3/4 x 17 5/8"
1125-4-500		1/2"	500	3,000	58	41 1/2 x 18 3/4 x 17 5/8"
1125-5-100		3/4"	100	3,000	42	26 3/4 x 18 3/4 x 17 5/8"
1125-5-175		3/4"	175	3,000	50	32 3/4 x 18 3/4 x 17 5/8"
1125-5-200		3/4"	200	3,000	55	38 3/4 x 18 3/4 x 17 5/8"
1125-5-250		3/4"	250	3,000	59	42 3/4 x 18 3/4 x 17 5/8"
1125-6-100		1"	100	3,000	69	44 1/2 x 18 1/2 x 17 5/8"

## CHOICE OF MOTORS



## 1125-E SERIES

- Equipped with 1/3HP 12V DC electric motor
- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 1" models)
- Swivel Seals: NITRILE (AFLAS on 1" models)
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap
- All welded steel "A" frame construction for superior reel structure
- A solid steel halo is welded to the disc for a direct gear driven motor.

MODEL	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125-4-100-E	1/2"	100	3,000	49	18 x 19 1/4 x 17 3/4"
1125-4-200-E	1/2"	200	3,000	52	24 x 19 1/4 x 17 3/4"
1125-4-325-E	1/2"	325	3,000	61	30 x 19 1/4 x 17 3/4"
1125-4-500-E	1/2"	500	3,000	71	40 x 19 1/4 x 17 3/4"
1125-5-100-E	3/4"	100	3,000	55	24 1/4 x 19 1/4 x 17 3/4"
1125-5-175-E	3/4"	175	3,000	63	30 1/4 x 19 1/4 x 17 3/4"
1125-5-200-E	3/4"	200	3,000	68	36 1/4 x 19 1/4 x 17 3/4"
1125-5-250-E	3/4"	250	3,000	72	40 1/4 x 19 1/4 x 17 3/4"
1125-6-100-E	1"	100	3,000	82	40 3/4 x 19 1/8 x 17 1/2"



## ROLLER BRACKETS FOR USE WITH 1125 SERIES

- Specify drum width
- 4-way enclosed pinch-proof stainless steel rollers are 1" in diameter supported by powder coated steel brackets
- 3-way open spool roller assembly with 1.5" chrome-plated machined steel spools and 1.5" stainless steel tubing bottom roller and powder coated steel brackets

PART NO.	DESCRIPTION	ADDED WEIGHT.
15353	4-way top rewind roller bracket	10
15358	4-way top rewind (ceiling mount) roller bracket	10
15354	4-way bottom rewind roller bracket	10
15353-P	4-way top rewind roller bracket	10
15359	3-way top rewind roller bracket	14
15362	3-way bottom rewind roller bracket	14



## PORTABLE HOSE REEL CART FOR USE WITH 1125 SERIES

- Steel round handle detaches for compact storage. Steel front legs with rubber feet prevent sliding.
- High grade ball bearing with hardened cup.
- 1/2" diameter steel axle. Solid 8" rubber tires. For 8" semi-pneumatic tires order model #PRP.

PART NO.	DESCRIPTION	APRX. LBS.
PR-1125-6	Portable Cart to be used with 1125-4-100 & 1125-5-50	17
PR-1125-12	Portable Cart to be used with 1125-4-200	17



## 100 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- Solid one piece, heavy gauge steel "U" shaped frame
- Open drum design for no hassle hose wrap

MODEL	I.D.	FT.	PSI	APRX. LBS.	W x H x L
112-3-50	3/8"	50	4,000	15	14 1/2 x 13 x 12"
112-3-100	3/8"	100	4,000	19	18 1/4 x 13 x 12"
112-3-150	3/8"	150	4,000	21	22 3/4 x 13 x 12"
117-3-250	3/8"	250	4,000	30	18 1/4 x 18 x 17"
117-3-400	3/8"	400	4,000	33	22 3/4 x 18 x 17"
117-3-550	3/8"	550	4,000	35	28 1/4 x 18 x 17"
112-4-75	1/2"	75	4,000	21	22 3/4 x 13 x 12"
117-4-225	1/2"	225	4,000	31	22 3/4 x 18 x 17"
117-4-350	1/2"	350	4,000	37	28 1/4 x 18 x 17"
117-5-100	3/4"	100	4,000	35	23 1/4 x 18 x 17"



## DM SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- High quality three piece 1-1/4" steel tube frame structure
- Solid 8" rubber tires for easy transport
- Rubber front feet prevent reel from slipping forward

MODEL	I.D.	FT.	PSI	APRX. LBS.	W x H x L
117-3-200-DM	3/8"	200	4,000	37	19 x 36 1/4 x 21"
117-4-225-DM	1/2"	225	4,000	39	23 1/2 x 36 1/4 x 21"



## CM SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- High quality three piece 1" steel tube frame structure
- Hose Control bar prevents hose from slipping off the discs

MODEL	I.D.	FT.	PSI	APRX. LBS.	W x H x L
112-3-100-CM	3/8"	100	4,000	18	18 1/2 x 14 3/4 x 13 1/8"
112-3-150-CM	3/8"	150	4,000	22	23 x 14 3/4 x 13 1/8"
117-4-225-CM	1/2"	225	4,000	28	23 x 18 1/2 x 18"

This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.