





ACCESSORIES *HAND CRANK & MOTORIZED REELS*

ROLLER BRACKETS



4-WAY ROLLER BRACKETS

	PART NO.	AVAILABLE FOR SERIES				
		1125	1175	1185	1195	1275
 <p>Top Rewind 4-way enclosed pinch-proof stainless steel rollers are 25 mm in diameter supported by powder coated steel brackets. Specify drum width. Weight: 4.5 Kg.</p>	15353*	•				•
	15355* 1275W-C					•
	15357*		•			
	15368* 711 mm disc size					•
	15368-1* 813 mm disc size					•
	15369* 610 mm disc size				•	
 <p>Top Rewind CEILING MOUNT APPLICATIONS 4-way enclosed pinch-proof stainless steel rollers are 25 mm in diameter supported by powder coated steel brackets. Specify ceiling mount & specify drum width. Weight: 4.5 Kg.</p>	15358*	•				•
	15356*		•			
 <p>Bottom Rewind 4-way enclosed pinch-proof stainless steel rollers are 25 mm in diameter supported by powder coated steel brackets. Specify drum width. Weight: 4.5 Kg.</p>	15354*	•				•
	15037*		•			
	15370-1*				•	
 <p>Top Rewind Extension 4-way enclosed pinch-proof stainless steel rollers are 25 mm in diameter supported by powder coated steel brackets. Specify drum width. Weight: 4.5 Kg.</p>	15353-P*	•				

*Take the drum width dimension, convert to inches & add as the suffix to the part number

EXAMPLE: An 1125-4-200 reel drum width is **12"**. Order part number: **15353-12**


3-WAY ROLLER BRACKET ASSEMBLIES

	PART NO.	AVAILABLE FOR SERIES			
		1125	1175	1185	1275
 <p>Top Rewind 3-way open spool roller assembly with 38 mm chrome-plated machined steel spools and 38 mm stainless steel tubing bottom roller and powder coated steel brackets. Specify drum width. Weight: 6 Kg.</p>	15359*	•			•
	15360* 610 mm disc size			•	•
	15361* 711 mm disc size				•
 <p>Bottom Rewind 3-way open spool roller assembly with 38 mm chrome-plated machined steel spools and 38 mm stainless steel tubing bottom roller and powder coated steel brackets. Specify drum width. Weight: 6 Kg.</p>	15362*	•			•
	15363* 610 mm disc size			•	•
	15364* 711 mm disc size				•

*Take the drum width dimension, convert to inches & add as the suffix to the part number

EXAMPLE: An 1125-4-200 reel drum width is **12"**. Order part number: **15359-12**




1125 SERIES STACKING BRACKET

	PART NO.	AVAILABLE FOR SERIES	
		1125	1125WCL
 <p>Top Rewind Stack your 1125 Series reels for double the storage in the same work area. Powder coated crinkle black, steel construction. Weight 3 Kg.</p>	7480	•	•

*Take the drum width dimension, convert to inches & add as the suffix to the part number

EXAMPLE: An 1125-4-200 reel drum width is **12"**. Order part number: **7480-12**


HOSE GUIDES

	PART NO.	AVAILABLE FOR SERIES		
		1125	1175	1185
 <p>Pivoting Hose Guide Heavy gauge powder coated steel arm & pivot mount w/5 locking positions. Stainless steel enclosed 4-way roller system and zinc plated axle for non-corrosive performance. Specify drum width. (For motor options E & ED only). Weight: 8 Kg.</p>	15732 Bottom Return	•		
	15733 Top Return	•		
 <p>Pivoting Hose Guide HD Heavy gauge powder coated steel arm & pivot mount w/ 5 locking positions. Large 25 mm diameter pivot shaft. Sealed precision bearings support pivot shaft & chrome-plated billet aluminum guide rollers. Specify drum width. (For motor options E & ED only). Weight: 8 Kg</p>	15728 Bottom Return		•	•
	15729 Top Return		•	
	15730 Top Return			•
 <p>Sliding Hose Guide 4-way, solid black delrin roller assembly, smooth tapered handle, non-corrosive zinc plated solid rods, heavy gauge "CPC" powder coated steel framing, specify drum width. Weight: 4 Kg.</p>	15734	•		

MODEL UPGRADES & ADDITIONS

	PART NO.	AVAILABLE FOR SERIES				
		1125	1175	1185	1195	1275
 <p>Spring Loaded Lock Pin The spring-loaded lock pin assembly is designed to lock and secure the reel, even in mobile conditions over rough terrain</p>	20843	•	•	•	•	•
	7406	•				
 <p>Gear Guards Guards beveled gears or chain and sprocket from dirt and foreign matter, while also protecting operator from injury.</p>	7700 610 mm disc size		•			
	8176				•	
	8176-1 610 mm disc size				•	
	8176-2 711 mm disc size				•	
 <p>Brawny Reel Upgrade Available for 1125 Series for 207 BAR (BX-) or 345 BAR (BH-) - 10 gauge plates welded into each disc to keep them from bowing. - Prevents deformation and eventual crushing of the drum that can be caused by hose pressure - The center drum has been thickened from 16 ga to 14 ga.</p>	Prefix model BX-	•				
	Prefix model BH-	•				
 <p>High Temperature Drag Brake For 13 mm models</p>	7429-1-4	•				
	High Temperature Drag Brake For 19 mm models	7429-1-5	•			
 <p>Wand Holder - Lightweight aluminum construction with black CPC™ powder finish. - 610 mm long with a 41 mm diameter, ideal to store pressure washing guns and other spraying devices. - Left, right, front and rear sides mount configuration.</p>	15735	•				

GARDEN HOSE KIT

	PART NO.	AVAILABLE ON
		1/2" Plumbing On Any Reel
 <p>Garden Hose Kit You are able to connect any hose to a reel with 13 mm plumbing. You will be able to use any garden hose for everything from watering plants to washing your car. Kit includes: NPT to garden hose adaptor & adaptor hose.</p>	15717	•