


PURE FLOW SERIES

BREATHING AIR & CLEAN FLUID HOSE REELS



COXREELS® Pure Flow Series is offered in spring rewind, hand crank and motorized retractions. All Pure Flow hose reels come standard equipped with stainless steel air/fluid paths and stainless steel swivels with non-toxic, food quality grease, ensuring clean, non-contaminated, safe and reliable transfer of breathing air, potable water or other clean fluids.

PURE FLOW EZ-P SERIES

Models with hose are for air or water service with a maximum temperature 150° F. Models less hose can be used for air, water or oil. **Note: Do not exceed listed hose O.D. to obtain maximum length.**

| LESS HOSE | | | | | | SIZE INDEX |
|---------------------|------|------|-----|------|------------|------------|
| MODEL | I.D. | O.D. | FT. | PSI | APRX. LBS. | |
| EZ-P-BLL-350 | 3/8" | 5/8" | 50 | 300 | 43 | 1 |
| EZ-P-BHL-350 | 3/8" | 5/8" | 50 | 6000 | 43 | 1 |

PURE FLOW EZ-T SERIES

Models with hose are for air or water service with a maximum temperature 150° F. Models less hose can be used for air, water or oil. **Note: Do not exceed listed hose O.D. to obtain maximum length.**

| LESS HOSE | | | | | | SIZE INDEX |
|----------------------|------|------|-----|------|------------|------------|
| MODEL | I.D. | O.D. | FT. | PSI | APRX. LBS. | |
| EZ-T-BLL-3100 | 3/8" | 5/8" | 100 | 300 | 85 | 2 |
| EZ-T-BHL-3100 | 3/8" | 5/8" | 100 | 6000 | 85 | 2 |

PURE FLOW 100 SERIES

| LESS HOSE | | | | | | SIZE INDEX |
|-----------------|------|------|-----|-------|------------|------------|
| MODEL | I.D. | O.D. | FT. | PSI | APRX. LBS. | |
| 112P-3-8 | 3/8" | 5/8" | 100 | 4,000 | 19 | 3 |

PURE FLOW CM SERIES

| LESS HOSE | | | | | | SIZE INDEX |
|--------------------|------|------|-----|-------|------------|------------|
| MODEL | I.D. | O.D. | FT. | PSI | APRX. LBS. | |
| 112P-3-8-CM | 3/8" | 5/8" | 100 | 4,000 | 18 | 3 |

PURE FLOW 1125 SERIES

| LESS HOSE | | | | | | | | | | SIZE INDEX |
|-------------------|--------------|------|-----|-----------------------------------|------|-----|-----------------------------|-------|------------|------------|
| MODEL | STANDARD CAP | | | OPTIONAL CAP. Reducer required | | | INLET SWIVEL & OUTLET RISER | PSI | APRX. LBS. | |
| | I.D. | O.D. | FT. | I.D. | O.D. | FT. | | | | |
| 1125P-4-6 | 1/2" | 7/8" | 100 | 3/8" | 3/4" | 140 | 1/2" F NPT | 6,000 | 36 | 4 |
| 1125P-4-8 | 1/2" | 7/8" | 150 | 3/8" | 3/4" | 200 | 1/2" F NPT | 6,000 | 37 | 5 |
| 1125P-4-12 | 1/2" | 7/8" | 200 | 3/8" | 3/4" | 300 | 1/2" F NPT | 6,000 | 39 | 6 |

MOTOR OPTIONS

When ordering, suffix the model number with selection below. *Add 5 lbs to ship weight if reel is crated

| SUFFIX | TYPE | DESCRIPTION | ADD ON APRX. LBS* |
|-----------|-----------------------------|--------------------------------|-------------------|
| A | AIR - #4 GAST | COMP. AIR MOTOR | 8 |
| E | ELEC. - 12V DC | 1/3 HP REW. REV. TYPE | 13 |
| EB | ELEC. - 24V DC | 1/2 HP REW. REV. TYPE | 26 |
| ED | ELEC. - EXPL. PRF. - 12V DC | 1/2 HP REW. REV. TYPE | 26 |
| EA | ELEC. - EXPL. PRF. | 115V 1/2 HP REW., AC REV. TYPE | 26 |
| H | HYDRAULIC | END PORTED 9/16-18 UNF REV. | 6 |

REEL DIMENSIONS

Technical Data Sheets Available On Website

| SIZE INDEX | W | | H | | L | X | Y | | M | N | Ø | Dw |
|------------|-----------------------|------------|----------------|---------|---------|---------|----------------|-------|----------|-----|----------|--------|
| | CRANK / ELEC / SPRING | AIR / HYD. | CRANK / SPRING | MOTOR | | | CRANK / SPRING | MOTOR | | | | |
| 1 | 7 1/8" | - | 18 5/8" | - | 17 1/8" | 6" | 6" | - | 4" | 5" | 1 11/8" | 3 3/4" |
| 2 | 9 3/8" | - | 25 1/2" | - | 24" | 8" | 9" | - | 7" | 8" | 1 5 3/4" | 4 1/2" |
| 3 | 18 1/4" | - | 13" | - | 12" | 9 1/2" | 6" | - | 5 1/2" | 3" | 5 1/2" | 8" |
| 4 | 19 3/4" | 17" | 18 5/8" | 19 1/4" | 17 5/8" | 11 3/8" | 15 3/8" | 16" | 9 7/16" | 10" | 6 1/4" | 6" |
| 5 | 21 3/4" | 19" | 18 5/8" | 19 1/4" | 17 5/8" | 13 3/8" | 15 3/8" | 16" | 11 7/16" | 10" | 6 1/4" | 8" |
| 6 | 25 3/4" | 23" | 18 5/8" | 19 1/4" | 17 5/8" | 17 3/8" | 15 3/8" | 16" | 15 7/16" | 10" | 6 1/4" | 12" |

Overall Dimensions

Base

Mounting Pattern

Drum

- See page 11 For P Series dim drawing
- See page 13 For T Series dim drawing
- See page 54 For 100 Series dim drawing

- See page 55 For CM Series dim drawing
- See page 58 For 1125 Series dim drawing

PURE FLOW SERIES :: REEL SPECIFICATIONS

SWIVEL

- Non-corrosive stainless steel air/fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- Safely store respiratory air hose lines for low or high pressure breathing air systems
- Safely store potable water hose lines for drinking water systems
- Safely store any hose requiring sanitized & non-contaminated fluid transfer application
- Each of these reels is built of their standard series with their own unique features & benefits

RETRACTION

- See page 11 for P Series retraction features
- See page 13 for T Series retraction features
- See page 36 for 100 Series retraction features
- See page 37 for CM Series retraction features
- See page 40 for 1125 Series retraction features

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Low Pressure Breathing Air Systems
- High Pressure Breathing Air Systems
- Fire Rescue
- Medical & Hospital Air Services
- Mining/Tunneling Operations
- Pharmaceutical Manufacturing
- Marine/Docks/Offshore
- High Pressure Cylinder Filling (SCUBA/SCBA)
- Shot Blasting
- Tank Cleaning
- Spray Painting
- Hazardous Site Cleanup
- Commercial Kitchens
- Pre-Rinse
- Potable Water
- Bulk Food
- Food Grade Washdown
- Food & Chemical Processing Plants

ACCESSORIZE YOUR REEL :: PG 50

- O-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories



SPRING DRIVEN

HAND CRANK