HAND CRANK & MOTORIZED POWER CORD REELS

COXREELS® 1125PCL Series professional-grade hand crank and motorized cord reels feature the industry preferred design including a drum-located, easy to access slip ring assembly for simple routine maintenance and a sturdy all-welded "A" frame built to efficiently handle the most demanding of tasks. The unique permanently lubricated and self-aligning pillow block bearings at each end of the drum allow smooth rotation and are specifically designed for rough, heavy-duty applications. These innovative models handle long length of 12/3 Gage or 10/3 Gage S0 type power cord.

1125PCL SERIES MODELS


	LESS CORD					
MODEL	12/3 SO	10/3 SO	VOLTS	AMPS	APRX. LBS.	SIZE INDEX
1125PCL-8-X	250'	200'	600	30	35	1
1125PCL-8M-X	250'	200'	600	45	35	1


- SUFFIX "X" OPTIONS


	/hen ordering, substitute the "X" with selection below. Add 5 lbs to ship weight if reel is crated.								
SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. LBS*						
A	AIR - #4 GAST	COMP. AIR MOTOR	8						
E	ELEC 12V DC	1/3 HP REW. REV. TYPE	13 13 26						
EF	ELEC 24V DC	1/3 HP REW. REV. TYPE							
EB	ELEC 24V DC	1/2 HP REW. REV. TYPE							
ED	ELEC EXPL. PRF 12V DC	1/2 HP REW. REV. TYPE	26						
EA	ELEC EXPL. PRF.	115V 1/2 HP REW., AC REV. TYPE	26						
н	HYDRAULIC	END PORTED 9/16-18 UNF REV.	6						
C	DIRECT HAND CRANK	STANDARD HAND CRANK	3						

REEL DIMENSIONS Technical Data Sheets Available On Website

	W		H				Y				
SIZE INDEX	CRANK	ELEC.	AIR / HYD.	CRANK	ELEC.	L	X	CRANK	ELEC.	Ø	Dw
1	211⁄2"	215⁄8"	187⁄8"	181⁄2"	19½"	171⁄2"	133⁄8"	15 ¹ ⁄4"	16"	81⁄2"	8"
	Overall Dimensions					— Base —		Drum —			







COXREELS® 1125PCL FEATURES



All Internal Components

 Drum-located slip ring assembly with easy access covers for simple routine maintenance.



1125PCL SERIES

1125PCL SERIES :: REEL SPECIFICATIONS

SLIP RING

- Drum-located slip ring assembly with easy to access cover for simple routine maintenance
- Available with 30 Amps or 45 Amps, 600 Volt rated slip ring assembly (see chart)

DESIGN & STRUCTURE

- All welded steel "A" frame construction to strengthen the reel structure
- Narrow width for convenient installation in restricted spaces
- \bullet Permanently lubricated self-aligning pillow block bearings for trouble-free & smooth rotation
- "Cable Keeper" to prevent the lead cable from whipping or twisting
- Adjustable tension brake to prevent "free-wheeling" during operation
- Long-handled locking pin to secure reel from rotation during transport or storage

RETRACTION

- Reliable direct gear drive on motor driven models
 NO CHAIN
- Solid steel direct hand crank with smooth round handle
- See Motor Options Chart

SIGNATURE FEATURES


- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Power Tools
- Light Source
- General Industrial
- Manufacturing Plants &
- Facilities

ACCESSORIZE YOUR REEL .: Pg 50

- Roller Brackets
- Assorted Reel Accessories





HAND CRANK

MOTORIZED