SS 100, 1125 & 1175 SERIES STAINLESS STEEL HAND GRANK & MOTORIZED HOSE REELS



SS SERIES - HAND CRANK/ MOTORIZED :: REEL SPECIFICATIONS SWIVEL

- · Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- · Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- · Choice of stainless steel finish includes:
- "-SP" Standard unpolished "as manufactured" stainless steel finish
- "-SS" Electro-polished stainless steel finish
- · Each of these reels is built of their standard series with their own unique features & benefits

RETRACTION

- · See page 36 for 100 Series features
- See page 40 for 1125 Series features
- · See page 41 for 1175 Series features

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Corrosive Environments
- · Hygienic Environments
- Fire Suppression

MOTORIZED

HAND CRANK

- Medical Services
- Marine/Docks/Offshore · Manufacturing Plants &
- Facilities
- Pulp & Paper Plants Food & Chemical
- **Processing Plants**

- · 0-Rings & Swivels
- Roller Brackets
- · Stacking Brackets

- · Bottling Plants
- Dairies
- Meat Packing
- Grocery Stores
- Restaurants & Commercial Kitchens
- Water Treatment & Supply
- Petrochemical
- Food Grade Washdown

ACCESSORIZE YOUR REEL .: PG 50

Assorted Reel Accessories

· Hoses

COXREELS® SS Series "Stainless Steel" hand crank hose reels have similar features to
their related series, but are constructed of high quality electro-polished stainless steel with
stainless steel fluid paths. They offer clean, non-corrosive performance in applications that require it, such
as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

SS 100 SERIES - Hand Crank

LESS HOSE									
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	SIZE INDEX			
112-4-75-SS	1⁄2"	7⁄8"	75	4000	21	1			
117-4-225-SS	1/2"	7⁄8"	225	4000	31	2			
117-5-100-SS	3⁄4"	1 ¹ ⁄4"	100	4000	36	3			

SS100 Series is only available in SS finish

SS 1125 SERIES - Hand Crank & Motor Driven

LESS HOSE										
MODEL	STANDARD CAP			OPTIONAL CAP. Reducer required			INLET SWIVEL & OUTLET	PSI	APRX.	SIZE INDEX
	I.D.	0.D.	FT.	I.D.	0.D.	FT.	RISER		LBS.	
1125-4-100- <mark>X</mark>	1⁄2"	7⁄8"	100	3⁄8"	3⁄4"	140	1⁄2" F NPT	3,000	36	4
1125-4-200- <mark>X</mark>	1⁄2"	7⁄8"	200	3⁄8"	3⁄4"	300	1⁄2" F NPT	3,000	39	5
1125-5-100- <mark>X</mark>	3⁄4"	11⁄4"	100	1⁄2"	7⁄8"	200	3⁄4" F NPT	3,000	42	6
1125-5-200- <mark>X</mark>	3⁄4"	11⁄4"	200	1⁄2"	7⁄8"	450	3⁄4" F NPT	3,000	55	7
L	Designa	ate either S	SP or SS	for choi	ice of finis	h				

SS 1175 SERIES - Hand Crank & Motor Driven

LESS HOSE											
MODEL	ST/	andard (CAP		FIONAL (ducer requi		INLET SWIVEL & OUTLET	PSI	aprx. Lbs.	SIZE INDEX	
	I.D.	0.D.	FT.	I.D.	0.D.	FT.	RISER				
1175-6-100- <mark>X</mark>	1"	1 ⁷ ⁄16"	100	3⁄4"	1 ¹ ⁄4"	150	1" F NPT	3,000	70	8	
1175-6-200- <mark>X</mark>	1"	17⁄16"	200	3⁄4"	1 ¹ /4"	300	1" F NPT	3,000	83	9	
Designate either SP or SS for choice of finish											

MOTOR OPTIONS When ordering, suffix the model number with selection below. *Add 5 lbs to ship weight if reel is crated

SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. LBS*								
A	AIR - #4 GAST	COMP. AIR MOTOR	8								
E	ELEC 12V DC	1/3 HP REW. REV. TYPE	13								
EB	ELEC 24V DC	1/2 HP REW. REV. TYPE	26								
ED	ELEC EXPL. PRF 12V DC	1/2 HP REW. REV. TYPE	26								
EA	ELEC EXPL. PRF.	115V 1/2 HP REW., AC REV. TYPE	26								
Н	HYDRAULIC	END PORTED 9/16-18 UNF REV.	6								
C	FRONT HAND CRANK	BEVEL GEARED CRANK	3								

REEL DIMENSIONS Technical Data Sheets Available On Website

	W			I	Н			Y			
SIZE INDEX	CRANK	ELEC.	AIR / HYD.	CRANK	ELEC.	L	Х	CRANK	ELEC.	Ø	Dw
1	223⁄4"	-	-	13"	-	12"	14"	6"	-	51⁄2"	12 ¹ /2"
2	223⁄4"	-	-	18"	-	17"	14"	6"	-	51⁄2"	12½"
3	231⁄4"	-	-	18"	-	17"	14"	6"	-	51⁄2"	12 ¹ /2"
4	19 ¹ /2"	19 ³ ⁄4"	17"	18 ³ ⁄4"	19 ¹ /4"	175⁄8"	11 ³ ⁄8"	15 ³ ⁄8"	16"	6 ¹ /4"	6"
5	251⁄2"	25 ³ ⁄4"	23"	183⁄4"	19 ¹ /4"	175⁄8"	173⁄8"	15 ³ ⁄8"	16"	6¹⁄4"	12"
6	263⁄4"	26"	233⁄8"	183⁄4"	19 ¹ /4"	175⁄8"	173⁄8"	15 ³ ⁄8"	16"	6¹⁄4"	12"
7	383⁄4"	38"	353⁄8"	183⁄4"	19 ¹ /4"	175⁄8"	293⁄8"	15 ³ ⁄8"	16"	6¹⁄4"	24"
8	281⁄8"	26"	24 ¹ /2"	261⁄8"	26 ¹ /8"	24"	17"	201⁄8"	201⁄8"	101⁄2"	11½"
9	36 ⁵ ⁄8"	34 ¹ /2"	33"	26 ¹ /8"	26 ¹ /8"	24"	25 ¹ /2"	20 ¹ /8"	20 ¹ /8"	10 ¹ /2""	20"
			- Overall Di	mensions-		— Base —		Dru	im ——		





