








MOUNTING & ROLLER BRACKETS

PART NO.	REEL SERIES									
	P	SHI, MP & HP	T	C	EN	PC	P-W & SHW	P-WC	Alumi-Pro®	Nitro-Pro®
 Swing Bracket For vertical surface mounting, allows reel to swing 180°. Powder coated crinkle black 3/16" steel. Weight: 5 lbs.	15720	•	•			•	•	•	•	•
15725			•	•						
 Swivel Bracket For horizontal surface mounting, ball bearing rotation, allows reel to swivel 345°. Powder coated crinkle black heavy gauge steel. Weight: 6 lbs. NOT FOR USE IN CEILING APPLICATIONS.	15721	•	•	•	•	•	•	•	•	•
 EZ-Up Bracket Reel easily slides in & out for easy overhead mounting. Use as an alternative to the #MR-1. Must be ordered with #15724 for "I" or "H" beam installations. Weight: 6.5 lbs.	15723	•	•	•	•	•	•	•	•	•
 EZ-Up "I" or "H" Beam Adapter Must be ordered with #15723. Powder coated crinkle black, all steel construction. Weight: 5 lbs.	15724	•	•	•	•	•	•	•	•	•
 Mounting Bracket For overhead mounting, fits 3" to 8 1/2" flange on "I" or "H" beam. Powder coated crinkle black 3/16" bent steel. Weight: 13 lbs.	MR-1	•	•			•	•	•	•	•
MRT-1			•	•						
 4-Way Roller Bracket Heavy gauge steel, powder coated Corexels blue (4RB) Available in stainless steel (4RB-SS). Weight: 1 lbs.	4RB 1/4"-3/4"	•	•	•	•	•	•	•	•	•
4RB-SS 1/4"-3/4"		•	•	•	•	•	•	•	•	•


S SERIES MOUNTING & ROLLER BRACKETS

PART NO.	S SERIES MODELS			
	SR13 & SL13	SR15 & SL15	SR17 & SL17	SR19 & SL19
 Dual Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 5 lbs.	15726-13	•		
15726-15		•		
15726-17			•	
15726-19				•
 Single Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 2 lbs.	SMB1	•	•	
SMB2			•	
SMB3				•


PVC INLET HOSE ASSEMBLIES

PART NO.	FITTINGS	I.D.	LENGTH	PSI	
	5150-1.5	1/4" Male x Female NPT	1/4"	18"	300
5153-1.5	3/8" Male x Female NPT	3/8"	18"	300	
5154-1.5	1/2" Male x Female NPT	1/2"	18"	300	
5155-1.5	3/4" Male x Male NPT	3/4"	18"	300	
5224-1.5	3/8" Male x Male NPT	3/8"	18"	3000	
5256-1.5	1/2" Male x Male NPT	1/2"	18"	2500	
5290-1.5	3/4" Male x Male NPT	3/4"	18"	1500	
5304-1.5	1/4" Male x Male NPT	1/4"	18"	5000	
5336-1.5	3/8" Male x Male NPT	3/8"	18"	4000	
15717	Garden 3/4" NPTM (w/Part #10781) x 3/4" NP	3/4"	48"	300	
5423-1.5	Twin Grade R 1/8" NPTM x BB 9-16 UNF	1/4" Twin	18"	200	
5424-1.5	"T" Grade Twin Grade R 1/8" NPTM x BB 9-16 UNF	1/4" Twin	18"	200	


90° ELBOWS

PART NO.	FITTING THREAD	I.D.	PSI	
	6088	Brass LP Male x Female NPT	1/4"	300
208	Brass LP Male x Female NPT	3/8"	300	
222	Brass LP Male x Female NPT	1/2"	300	
385	Brass LP Male x Female NPT	3/4"	300	
500	Steel MP Male x Female NPT	3/8"	3000	
1671	Steel MP Male x Female NPT	1/2"	3000	
15014	Steel MP Male x Female NPT	3/4"	1250	
616	Steel HP Male x Female NPT	1/4"	5000	
617	Steel HP Male x Female NPT	3/8"	5000	

HOSE STOPS & GUARDS


HOSE STOPS PART NO.	HOSE GUARD PART NO.	HOSE		OVERALL	
		I.D.	O.D.		
	131	237-1	1/4"	1/2"	2 1/2"
633	237-1		1/4" Twin Line		3 1/2"
131-3	237-1	3/8"	2 1/32"		2 1/2"
131-4	398-1	1/2"	3/4"		2 1/2"
254	-	1/2"	3/4"		3 1/2"
430	398-1	3/4"	1"		3 1/2"
20214	-	1"	1 9/16"		5"
20215	-	1 1/4"	1 11/16"		5"
20216	-	1 1/2"	2 1/16"		5"
20217	-	2"	2 9/16"		5"

BEND RESTRICTORS

ADD SUFFIX	I.D.	DESCRIPTION	PSI	
	-BxB	1/4"	Black PVC Bend Restrictor	
-BxB	3/8"	Black PVC Bend Restrictor		
-BxB	1/2"	Black PVC Bend Restrictor		

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing.

QUICK DISCONNECTS

PART NO.	I.D.	DESCRIPTION	CONNECTION	PSI	
	10759-1	1/4"	Quick Disconnect	NPT (F)	300
10759-2	3/8"	Quick Disconnect	NPT (F)	300	

Quick disconnect couplings thread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines. Conveniently connect, interchange, and secure pneumatic tools or other spraying devices to any air, water, chemical or other hose lines.

SPRING DRIVEN