

# SIDE MOUNT HOSE REELS FOR CABINET MOUNT

# EZ-S SERIES

**COXREELS® EZ-S Series** “Side Mount” spring driven hose reels for cabinet mount are compact, versatile and unique in the way they mount and operate. They feature a simple two-bolt mounting pattern for easy installation and detachment for multiple workstation applications. EZ-S Series is available for air/water, oil, grease, oxy-acetylene and T Grade gas welding hose. The 360° hose direction allows the user to operate the reel in any direction the job demands. Common applications include service units, tool benches, tool boxes, vertical walls and beams, vehicle lift systems, machine tools, service vehicles or any flat vertical surface.

## S SERIES LOW PRESSURE

Models with hose are for air or water service with a maximum temperature 150° F. Models less hose can be used for air, water or oil.  
**Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	MOUNT	I.D.	O.D.	FT.	PSI	APPR. LBS.	MODEL	APPR. LBS.	
<b>EZ-SR13-L125</b>	Right	1/4"	1/2"	25	300	18	<b>EZ-SR13L-L125</b>	14	<b>1</b>
<b>EZ-SL13-L125</b>	Left	1/4"	1/2"	25	300	18	<b>EZ-SL13L-L125</b>	14	<b>1</b>
<b>EZ-SR15-L135</b>	Right	1/4"	1/2"	35	300	23	<b>EZ-SR15L-L135</b>	17	<b>2</b>
<b>EZ-SL15-L135</b>	Left	1/4"	1/2"	35	300	23	<b>EZ-SL15L-L135</b>	17	<b>2</b>
<b>EZ-SR15-L325</b>	Right	3/8"	5/8"	25	300	23	<b>EZ-SR15L-L325</b>	17	<b>2</b>
<b>EZ-SL15-L325</b>	Left	3/8"	5/8"	25	300	23	<b>EZ-SL15L-L325</b>	17	<b>2</b>
<b>EZ-SR17-L350</b>	Right	3/8"	5/8"	50	300	32	<b>EZ-SR17L-L350</b>	25	<b>3</b>
<b>EZ-SL17-L350</b>	Left	3/8"	5/8"	50	300	32	<b>EZ-SL17L-L350</b>	25	<b>3</b>
<b>EZ-SR17-L430</b>	Right	1/2"	3/4"	30	300	34	<b>EZ-SR17L-L430</b>	29	<b>3</b>
<b>EZ-SL17-L430</b>	Left	1/2"	3/4"	30	300	34	<b>EZ-SL17L-L430</b>	29	<b>3</b>
<b>EZ-SR19-L450</b>	Right	1/2"	3/4"	50	300	37	<b>EZ-SR19L-L450</b>	29	<b>4</b>
<b>EZ-SL19-L450</b>	Left	1/2"	3/4"	50	300	37	<b>EZ-SL19L-L450</b>	29	<b>4</b>



Reel Orientation:  
Right Mount is shown with mounting base on the right side & hose payout from the top of the reel

## EZ-S SERIES :: REEL SPECIFICATIONS

### SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE

### DESIGN & STRUCTURE

- Side mount design for vertical flat surface, cabinet or enclosed space mounts
- 2-bolt mounting pattern easily mounts & detaches for temporary or permanent installation
- Solid one piece, heavy gauge 1/4" steel arm base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Hose control bar prevents hose from slipping off the discs

### EZ-COIL RETRACTION

- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length.
- Non-locking, less ratchet option available (add suffix **-BXC**)

### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

### POSSIBLE FIELDS OF APPLICATION

- Air/Water Services
- Pneumatic Tools
- Lubrication
- Chemical Fluid Transfer
- Welding Shops
- General Industrial
- Cabinet Mount
- Service / Mechanic / Utility Vehicles
- Construction Sites

### ACCESSORIZE YOUR REEL :: PG 17


- O-Rings & Swivels
- Hoses
- Assorted Reel Accessories

## REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Y	M
<b>1</b>	6"	14 1/4"	13"	2 1/2"	9 1/4"
<b>2</b>	6"	16 1/2"	15 1/4"	2 1/2"	10 1/4"
<b>3</b>	5 3/4"	18 1/4"	17"	2 1/2"	13"
<b>4</b>	7 1/2"	20 3/4"	19 1/2"	2 1/2"	14 1/4"

Overall Dimensions      Base      Mounting Pattern



## LET'S COMPARE

Conventional  
SPRING DRIVEN  
REELS



**SPEED**  
**WHIPPING**  
**IMPACT**

**25** ft./sec.  
**5-15** ft.  
**500** ft./lbs.

**5** ft./sec.  
**1** ft.  
**0-1** ft./lbs.

Up To **80%**  
Slower Retraction

Based on an independent evaluation performed by COXREELS. Depending on certain conditions, results may vary.

